

Series Nr	KMX-P5.9	KMX-P7.8	KMX-P10.4	KMX-P15.6
Pitch	P5.9	P7.8	P10.4	P15.6
Brightness				
Black Shell SMD	>5000cd/m ²	>5000cd/m ²	>5500cd/m ²	>5500cd/m ²
Distance	>5.9m	>7.8m	>10.4m	>15.6m
LED kind	SMD1921	SMD1921	SMD2727	SMD3535
Pixel Density	28224 /m ²	16384 /m ²	9216 /m ²	4096 /m ²
View Angle	140°/140°	140°/140°	140°/140°	140°/140°
Refreshrate	>3840hz	>3840hz	>3840hz	>3840hz
Module Size	250x500mm	250x500mm	250x500mm	250x500mm
Cabinet Size	500x1000mm	500x1000mm	500x1000mm	500x1000mm
Cabinet Res.	84x168px	64x128px	48x96px	32x64px
Drive Mode	1/7 scan	1/4 scan	1/2 scan	Static
Environment	IP65 / IP55	IP65 / IP55	IP65 / IP55	IP65 / IP55
Average Power	200W - 250W/m ²	200W - 250W/m ²	200W - 250W/m ²	200W - 250W/m ²
Voltage	100v-220v	100v-220v	100v-220v	100v-220v
Weight	11kg	11kg	11kg	13kg
Certified	EMC CE	EMC CE	EMC CE	EMC CE